

```
# $Id: formsweb.cfg,v 1.23 2002/01/25 06:51:41 oraforms Exp $
#
# -----
# formsweb.cfg - Forms Servlet default configuration file
# -----
# This file defines parameter values used by the FormsServlet (f90servlet)

# ****
# DEFAULT CONFIGURATIONS
# ****
#
# These are the default settings. Any of them may be overridden in the
# Named Configurations section. If they are not overridden, then the
# values here will be used.
# System Parameters cannot be overridden in the URL. User Parameters can.
#

#
# SYSTEM PARAMETERS
# -----
# These have fixed names and give information required by the Forms
# Servlet in order to function. They cannot be specified in the URL query
# string. But they can be overriden in a named configuration (see below).
# Some parameters specify file names: if the full path is not given,
# they are assumed to be in the same directory as this file. If a path
# is given, then it should be a physical path, not a URL.
#

baseHTML=base.htm
baseHTMLjinitiator=basejini.htm
baseHTMLjpi=basejpi.htm
baseHTMLie=baseie.htm

HTMLdelimiter=%

#
# WorkingDirectory defaults to <oracle_home>/forms90 if unset.
#
workingDirectory=
envFile=default.env

#
# The next parameter specifies how to execute the Forms applet under
# Microsoft Internet Explorer 5.x. Put IE=native if you want the
# Forms applet to run in the browser's native JVM.
#
IE=JInitiator
```

```
#  
# USER PARAMETERS  
# -----  
# These match variables (e.g. %form%) in the baseHTML file. Their values  
# may be overridden by specifying them in the URL query string  
# (e.g. "http://myhost.mydomain.com/servlet/f90servlet?form=myform&width=700")  
# or by overriding them in a specific, named configuration (see below)  
#  
#  
# 1) Runform arguments:  
#  
form=test.fmx  
userid=  
  
#  
# These settings support running and debugging a form from the Builder:  
#  
otherparams=debug=%debug% buffer_records=%buffer%  
debug_messages=%debug_messages% array=%array% query_only=%query_only%  
quiet=%quiet% render=%render% host=%host% port=%port% record=%record%  
tracegroup=%tracegroup% log=%log% term=%term%  
debug=no  
buffer=no  
debug_messages=no  
array=no  
query_only=no  
quiet=yes  
render=no  
host=  
port=  
record=  
tracegroup=  
log=  
term=  
  
#  
# 2) HTML page title, attributes for the BODY tag, and HTML to add before and  
#   after the form:  
#  
pageTitle=Oracle9iAS Forms Services  
HTMLbodyAttrs=  
HTMLbeforeForm=  
HTMLafterForm=
```

```
#  
# 3) Values for the Forms applet parameters:  
#  
serverURL=/forms90/l90servlet  
codebase=/forms90/java  
imageBase=DocumentBase  
width=650  
height=500  
separateFrame=false  
splashScreen=  
background=  
lookAndFeel=Oracle  
colorScheme=teal  
logo=  
formsMessageListener=  
recordFileName=  
  
serverApp=default  
  
#  
# The following archive settings are for  
# archive_jini - settings for JInitiator  
# archive_ie - settings for IE native JVM  
# archive - settings for all other cases (Java Plugin, Appletviewer, etc)  
#  
archive_jini=f90all_jinit.jar  
archive_ie=f90all.cab  
archive=f90all.jar  
  
#  
# Number of times client should retry if a network failure occurs. Only  
# change after having read the documentation.  
#  
networkRetries=0  
  
#  
# 4) Parameters for JInitiator (used with Windows clients)  
#  
  
#  
# Page displayed to Netscape users to allow them to download JInitiator.  
# If you create your own page, you should set this parameter to point to it.  
#  
jinit_download_page=/forms90/jinitiator/us/jinit_download.htm  
  
#
```

```
# Parameters related to the version of JInitiator.  
#  
jinit_classid=clsid:CAFECAFE-0013-0001-0013-ABCDEFABCDEF  
jinit_exename=jinit.exe#Version=1,3,1,13  
jinit_mimetype=application/x-jinit-applet;version=1.3.1.13  
  
#  
# 5) Parameters for the Java Plugin (used with non-Windows clients)  
#  
  
#  
# Page displayed to users to allow them to download the JPI  
# (NOTE: you should check this page and possibly change the settings)  
#  
jpi_download_page=http://java.sun.com/products/plugin/1.3/plugin-install.html  
  
#  
# Parameters related to the version of the Java Plugin  
#  
jpi_classid=clsid:8AD9C840-044E-11D1-B3E9-00805F499D93  
jpi_codebase=http://java.sun.com/products/plugin/1.3/jinstall-13-  
win32.cab#Version=1,3,0,0  
jpi_mimetype=application/x-java-applet;version=1.3  
  
#  
# 6) EM config parameter  
# Set this to "1" to enable Enterprise Manager to track Forms processes  
#  
em_mode=0  
  
#  
# 6) OID Config parameters (for Single Sign-On)  
#  
oid_formsid=%OID_FORMSID%  
oracle_home=e:\desuite9i  
  
# *****  
# NAMED CONFIGURATIONS  
# *****  
#  
# You may define your own specific, named configurations (sets of parameters)  
# by adding special sections as illustrated in the following examples.  
# Note that you need only specify the parameters you want to change. The  
# default values (defined above) will be used for all other parameters.  
# Use of a specific configuration can be requested by including the text  
# "config=<your_config_name>" in the query string of the URL used to run
```

```
# a form. For example, to use the sepwin configuration, you could issue
# a URL like "http://myhost.mydomain.com/servlet/f90servlet?config=sepwin".
#
#
# Example 1: configuration to run forms in a separate browser window with
#           "generic" look and feel (include "config=sepwin" in the URL)
#
[sepwin]
separateFrame=True
lookandfeel=Generic

#
# Example 2: configuration affecting users of MicroSoft Internet Explorer 5.x.
#           Forms applet will run under the browser's native JVM rather than
#           using Oracle JInitiator.
#
[ienative]
IE=native

#
# Example 3: configuration forcing use of the Java Plugin in all cases
#           (even if the client browser is on Windows)
#
[jpi]
baseHTMLJInitiator=basejpi.htm
baseHTMLie=basejpi.htm

#
# Example 4: configuration running the Forms ListenerServlet in debug mode
#           (debug messages will be written to the servlet engine's log file)
#
[debug]
serverURL=/forms90/l90servlet/debug
```